

MEDICAL COMPUTER HARDWARE

e-medic[™] Silence ST-M BTO

Powerful. Fanless. Medical computer.



The fanless **e-medic[™] Silence ST-M** computers are high performance medical PC systems, which are ideally suited for the long-term use in hospitals and doctor's surgeries. The use of the modern Intel[®] Skylake platform guarantees a fast and extreme efficient system with an average of 30W. Powerful processors in combination with an especially developed 4 channel heat pipe provide high performance with lowest noise level. Functions like Bios MAC Address Display, iAMT (Intel[®] Active-Managementtechnology), TPM and Wake on LAN enable a high safety standard with remote maintenance and remote analysis possibilities.

Ideal for:


Surgery/intensive care	*	*	*
Endoscopy	*	*	*
Diagnostics	*	*	*
Viewing	*	*	*
Patient environments	*	*	*

Advantages:

- Easy to clean maintenance-free, closed casing
- > Triple View 3 monitors can be connected
- Versatile installation possible on wall, VESA-mounting or support arms
- Small, compact and lightweight (4 kg)



MEDICAL COMPUTER HARDWARE



Technical Data	i3	i5	i7			
Processor	Intel [®] Skylake [™] i3-6100T	Intel [®] Skylake™ i5-6500T	Intel [®] Skylake™ i7-6700T			
	3.2 Ghz, 3 MB Cache	2.5-3.1 Ghz, 6 MB Cache	3.6 Ghz, 8 MB Cache			
Core	Dual-Core with Hyper Threading (HT)	Quad-Core	Quad-Core with Hyper Threading (HT)			
Mainboard	Fujitsu® with Intel® Q170 Chipset					
RAM	32 GB max., DDR4-2133 MHz (2x RAM slot) Dual Channel					
Hard Disks	120 GB SSD / 256 GB SSD / 512 GB SSD / 500 GB HDD / 1 TB HDD / 2 TB HDD					
Graphics	Intel [®] HD Graphics 530 (Direct X12) internal GPU, max. Resolution 4096x2304 (4K), Triple View, Video and 3D acceleration					
Supported Operating Systems	Windows [®] 7 Pro Windows [®] 8.1 Pro (not included)	Windows® 10 Pro				
External Interfaces	1x DVI-D, 2x DisplayPort, 4x USB 3.0, 4x USB 2.0, 2x PS/2, 2x RS-232, Audio In/Out					
LAN	2x RJ45 LAN: 1x Intel® i219LM / 1x Intel i210AT (10/100/1000mbit), iAMT, Wake on LAN					
Sound	Realtek ALC671 (HD Sound)					
Power Supply	external medical Power Supply 63 W					
Cooling System	4 channel heat pipe					
Housing	fanless, closed, aluminium / steel Mini-ITX, with additional potential earth pin					
Dimensions (WHD)	260x 85x 240 mm					
Weight	4 kg					
Temperature	+5°C up to +40°C (operating) -10°C up to +60°C (storage)					
Humidity	15 % - 85 % (operating, non-condensing) 5 % - 90 % (storage, non-condensing)					
Air Pressure	700 hPa - 1075 hPa (operating/ storage)				
Standards	CE, RoHS, EN 60601-1-2:2015; EN 55011:2009 + A1:2010; EN 61000-3-2:2006 + A1:2009 + A2:2009; EN 61000-3-3:2008; (DIN EN 60601-1 3.1 Edition - only power supply)					
Safety Functions	Infineon TPM V2.0, Bios MAC Address I USB Port Access Protection	Display, Recovery BIOS, Serial- /	καυκα			
Production Standard	Manufactured in Germany according to	ISO 9001				
Optional	DVD-RW Slot-In, WLAN, Bluetooth, Wir 3 years warranty, 5 years warranty	ndows® 10 Pro,	Your contact person for further questions and interest:			
Item No.:	2011375		Kauko Oy Juha Alanen			

Rev.5/03-19. Errors and omissions reserved.

juha.alanen@kauko.com +358 40 922 9142

Sales Manager